

up to 1500
rpm


MS-20A analog

Ideal for:

- mixing of chemical, laboratory and pharmaceutical materials
- heat-sensitive procedures in microbiology and biochemistry

Features:

- up to 1.500 rpm
- ceramic-coated aluminium plate 180x180 mm
- heat-, chemical- and acid-resistant
- no liquid can get into the body
- powder-coated aluminium body
- 30 mm stirrer bar included
- CE certified and unique serial number for tracing

Safety mechanism:

- operation LEDs

Controller:

- **PWM controller**



Stirrer bar included

Model	MS-20A
Body	powder-coated aluminium
Plate	ceramic-coated aluminium (heat-, chemical- and acid-resistant), 180x180 mm
Stirring capacity	max. 20 l
Speed	up to 1.500 rpm
Timer & alarm	99hr 59min (with Continuous run), error status and timer-end
Controller	superior linearity PWM Controller
Stirring bar	30 mm bar included, usable up to 50 mm bar
Permissible temperature & RH %	ambient temperature +5 ~ 50°C, 85% RH
Dimension & weight	206x307xh99 mm, 3.1 kg
Packaging size	400x280xh200 mm, 5 kg
Power supply	1 Phase AC 120V, 60 HZ or AC 230V, 50/60 Hz
Order number 230V	DH.WMS03122
Order number 120V	DH.WMS02122